

NBP-14570-BX PICMG 1.3 14-Slot Industrial Backplane



14-Slot Backplane with 1 PICMG 1.3 Slot, 7-PCI Slots, 1-PCIe x16, 4 x PCIe x4

Dimensions	317 mm (L) x 328 mm (W)
Slots	1 x PICMG 1.3 (SBC slot), 7 x PCI 32bit/33Mhz, 1 x PCIe x16, 4 x PCIe x4
I/O Interface	2 x USB 2.0 with 2 x 9 pin-header, 2 x SATA, 2 x 3-pin FAN, 1 x 6 Pin JST NEXCOM defined front I/O connector for power LED connector/power switch/reset button connector
Power Input	1 x 24-pin power connector, 1 x Terminal Block
Power Output	1 x 4-pin 12V AUX power connector to SBC



Environment	Operating temperature: 0°C to 60°C, Storage temperature: -20°C to 80°C Non-operating 5%~95%, non-condensing
Certifications	CE FCC Class A

NBP-1412P PICMG 1.0 14-Slot Industrial Backplane

14-Slot Backplane with 3-PICMG 1.0 Slots, 12-PCI

Dimensions	315 mm (L) x 260 mm (W)
Slots	3 x PICMG 1.0, 12 x PCI 32bit/33Mhz
Power Input	1 x 24-pin power connector, 1 x peripheral power connector, 1 x terminal block
Environment	Operating temperature: 0°C to 60°C., Storage temperature: -20°C to 80°C
Relative Humidity	Operating 10%~90%, non-condensing Non-operating 5%~95%, non-condensing
Certifications	CE FCC Class A

