

# NBP-14210 PICMG 1.3 14-Slot Industrial Backplane



## 14-Slot Backplane with 1 PICMG 1.3 Slot, 10-PCI Slots, 1-PCIe x16, PCIe x4

### Specifications

**Dimension** 328 mm (L) x 317 mm (W)

**Slots** 1 x PICMG 1.3 (SBC slot), 10 x PCI 32bit/33Mhz, 1 x PCIe x16, 1 x PCIe x4

**I/O Interface** 2 x USB 2.0 with 2 x 9 pin-header, 2 x SATA, 3 x 3-pin FAN, 1 x 6 Pin JST NEXCOM defined front I/O connector for power LED connector/power switch/ reset button connector

**Power Input** 1 x 24-pin power connector, 1 x 8-pin 12V AUX power connector, 1 x 4-pin 12V AUX power connector

**Power Output** 1 x 4-pin 12V AUX power connector to SBC

**Environment** Operating temperature: 0°C to 60°C,  
Storage temperature: -20°C to 80°C



Relative humidity:

Operating 10%~90%, non-condensing

Non-operating 5%~95%, non-condensing

**Certifications** CE FCC Class A

# NBP-14111 PICMG 1.3 14-Slot Industrial Backplane

## 14-Slot Backplane with 1 PICMG 1.3 Slot, 3-PCI Slots, 8-PCI-X & 1-PCIe x16

### Specifications

**Dimension** 328 mm (L) x 317 mm (W)

**Slots** 1 x PICMG 1.3 (SBC slot), 3 x PCI 32bit/33Mhz, 8 x PCI-X 64bit/66Mhz, 1 x PCIe x16

**I/O Interface** 4 x USB 2.0 with 2 x 9-pin header, 2 x SATA, 1 x IPMI, 1 x SMBUS, 1 x wake-up, 6 x 3-pin FAN, 1 x 6-pin JST NEXCOM defined front I/O connector for power LED connector/power switch/ reset button connector

**Power Input** 1 x 24-pin power connector, 2 x 8-pin 12V AUX power connector, 2 x 6-pin 3.3V power connector for PCI-X add-on, 1 x terminal block

**Power Output** 1 x 4-pin 12V AUX power connector to SBC, 1 x 4-pin power connector for system fan

**Environment** Operating temperature: 0°C to 60°C.,  
Storage temperature: -20°C to 80°C



Relative humidity:

Operating 10%~90%, non-condensing

Non-operating 5%~95%, non-condensing

**Certifications** CE FCC Class A