

PPC-5150 /PPC-5170 Pentium IV Panel/Rack Mount Computer with LCD



15" or 17" TFT LCD, 1-PCI Slot (with or without Touch Screen)



POS-478
Socket-478 full function
POS board with LCD/CRT
VGA, LAN, USB 2.0, 1394,
Audio

Specifications

- Socket 478 mainboard for Pentium IV and Celeron up to 533 MHz
- Panel or rack mount (or use VESA standard arm)
- Front panel meets NEMA & IP65
- 15" high brightness TFT LCD (PPC-5170)
 - Resolution: 1024 x 768
 - Brightness: 250 cd/m²
 - LCD MTBF: 50,000 hours
 - Backlight MTBF: 25,000 hours
- 17" high brightness TFT LCD (PPC-5170)
 - Resolution: 1280 x 1024
 - Brightness: 260 cd/m²
 - LCD MTBF: 50,000 hours
 - Backlight MTBF: 25,000 hours
- Bays: 1-slim 3.5" FDD, 1-slim CD-ROM, 1-2.5" HDD
- Accepts one half-size PCI add-on card
- Equipped with CPU cooling fan
- Standard 200 W. power supply with PFC
- Operating Temperature: 0~50° C
- Vibration: 5-17Hz, 0.1" double amplitude displacement, 17-500 Hz, 1.5 G acceleration peak-to-peak
- Shock: 10 G acceleration peak-to-peak
- Beige
- Dimensions: 410mm W x 309mm H x 102.4mm D (PPC-5150)
- Dimensions: 452mm W x 356mm H x 108.6mm D (PPC-5170)

Options:

- ARM-31
- RK-150 rack mount kit
- Touch screen

All specifications are subject to change without notice.

Panel or Rack Mount

